

### In the Specification

*Kindly replace paragraphs [0001] through [0013] with the following:*

#### Related Application

This is a §371 of International Application No. PCT/FR2005/000555, with an international filing date of March 8, 2005 (WO 2005/088950, published September 22, 2005), which is based on French Patent Application No. 04/50462, filed March 8, 2004.

#### Technical Field

~~The present invention~~This disclosure relates to the field of queues. ~~The present invention~~  
~~relates, more specifically, to the estimation of~~estimating call intents and recalls in a call ~~cent~~re~~center~~.

#### Background

Queue-based systems can be found in many business sectors. These consist, in general terms, of a system comprising one or several operators with the purpose of replying to customers that arrive in a random fashion. If, upon the arrival of a customer, no operators are available, the customer must wait in a queue before ~~[[he]]the call~~ can be answered. There are many examples in various fields of activity that illustrate this type of system. ~~By way of example, we can mention~~Examples include vehicles waiting to pay ~~thea~~ toll on a motorway, data packages waiting to be processed in a computer network, or customers calling a call ~~cent~~re~~center~~ and waiting for a customer service representative to answer them.

~~The prior art essentially knew solutions for estimating the waiting time in a call centre queue.~~

~~The prior art already knew, from US patent application US 5905793 (Lucent)~~US 5,905,793  
discloses a method for selecting calls on hold based on their anticipated waiting times. The maximum waiting time for callers to a call ~~cent~~re~~center~~ is reduced by selecting, for a representative that has just become available to answer a call, a high-priority call on hold, which will have to wait

longer than any other call on hold if it is not answered at that moment. Anticipated waiting times are calculated for the calls at the top of the non-empty queues of high-priority calls that match the skills of the representative. The anticipated waiting time of a call is calculated as being the current waiting time (elapsed) of the call plus the average progress rate for the calls in the call queue. The call with the longest anticipated waiting time is then chosen first and ~~[[is ]]~~transferred to the available representative ~~in order~~ to be processed. The process is repeated every time a representative becomes available.

~~The prior art also knew, from patent application PCT-WO 01/63894 (Siemens),~~discloses a system and ~~[[a ]]~~method that makes it possible to predict the waiting time for a caller to a call ~~cent~~center. The call ~~cent~~center defines a group of representatives for whom the caller may be placed in the queue. The choice of this group of representatives may depend on the specific skills of each representative, the type of service required by the customer, the priority of the caller, the time, the day of the week or any other conditions. An initial estimate of the waiting time can then be sent to the caller who was just placed in the queue. Given that the conditions of a caller can change dynamically, the position of a caller in the queue can also change, as can the group of available representatives. Periodic updates of the estimated waiting time can also be sent to the caller waiting in the queue. The waiting time for a caller can be calculated according to the average intervals that separate the arrival of recent calls to the call ~~cent~~center. An average time between arrivals can be calculated for the last several calls.

In another embodiment ~~of the invention~~, the waiting time for a caller can be calculated according to the calls placed in the queue and leaving the queue recently. A table of values,  $W_{nj}$ , is kept, in which each value indicates the  $j^{\text{th}}$  recent waiting time of calls arriving after  $n$  calls are already placed in the queue. This makes it possible to calculate an average value,  $W_n$ , for each  $n$  among all

the Wnj and to provide the caller with an estimated waiting time, according to the number of calls already in the queue at the time of the call.

~~The prior art also knew, from US patent application US 2001/0000458[[,]]~~ discloses a method of calculating the waiting time in a queue system for telephone routing. This method has the advantage of taking priorities among customers into consideration. ~~Having said that, this~~ That method requires a very large number of real-time measurements and information on the status of the system. ~~In order to apply this method, it~~ It is, for example, necessary to know the actual number of representatives that are answering calls. This ~~would require~~ requires the use of further equipment (CIT or Computer Integrated Telephony) in addition to the ACD (Automatic Call Dispatcher). ~~In the case of the invention, the~~ The routing takes place in the ACD alone and only a limited amount of information is known in real time.

~~However, these documents of~~ Thus, the prior art does not ~~refer to~~ address the problem of estimating the number of call intents, and merely assesses waiting times.

### Summary

This invention relates to a method of estimating call intents and recalls in a call center including (a) assessing  $N$  corresponding to a number of periods during which recall assessments are performed; (b) assessing  $\alpha_i$  representing a proportion of disconnected calls that call back during an  $i^{\text{th}}$  period following disconnection; (c) assessing  $\beta_i$  representing a proportion of abandoned calls that call back during an  $i^{\text{th}}$  period following abandonment; (d) assessing call status variables:  $Dec(p)$  representing the number of calls disconnected during a period  $p$ ;  $Abd(p)$  representing the number of calls abandoned during a period  $p$ ; and  $Recus(p)$  representing the number of calls received during period  $p$ ; (e) estimating the number of recalls,  $rappels(p)$ , during the period  $p$ , with

$$\underline{rappels(p) = \sum_{i=0}^N \alpha_i \cdot dec(p-i) + \beta_i \cdot abd(p-i)}, \text{ where } p-i \text{ represents a period that precedes } p \text{ of } i$$

periods; and (f) assessing the number of call intents during a period p,  $intentions(p) = re\acute{c}us(p) - rappels(p)$ .

This invention also relates to a system for estimating call intents and recalls in a call center including calculation equipment connected to equipment associated with call-answering stations, wherein the calculation equipment includes means for counting a number of disconnected calls *Dec*, a number of abandoned calls *Abd*, a number of received calls *Reçus* and calculation means for determining coefficients  $\alpha_i$ ,  $\beta_i$  and *N*, as well as calculation means for determining variables of the number of recalls and the number of call intents  $rappels(p) = \sum_{i=0}^N \alpha_i \cdot dec(p-i) + \beta_i \cdot abd(p-i)$  and

$intentions(p) = re\acute{c}us(p) - rappels(p)$ , where *N* corresponds to a number of periods during which an assessment of recalls takes place;  $\alpha_i$  represents a proportion of disconnected calls that call back during an  $i^{th}$  period following disconnection;  $\beta_i$  represents a proportion of abandoned calls that call back during an  $i^{th}$  period following abandonment; and  $p-i$  represents a period that precedes *p* of *i* periods.

#### Brief Description of the Drawings

The disclosure will be better understood from reading the following description, provided below by way of example made in reference to the appended figures, in which:

Fig. 1 shows the general principle of a call to the call center; and

Fig. 2 is a flowchart of the process of calling and of recalls for disconnections and abandonments.

## Detailed Description

~~Therefore, beyond the~~Beyond management of waiting times in accordance with the prior art, ~~the present invention, by allowing~~we employ a direct assessment of the number of call intents and recalls~~[[,]]~~to enable~~[[s]]~~ particularly efficient management of the call ~~centre~~center.

To do so, an evident method for assessing the number of call intents or of recalls in a given period ~~would~~may be to systematically list the identifier of each call received (for example, the telephone number). In this way, it is possible to determine, when a call arrives, whether it is a first call intent or a recall. If the call identifier is already listed and has not yet been answered then it is a recall. Otherwise, it is a first call intent.

~~The drawback of~~However, this approach ~~is that it requires~~uses rather considerable computer resources. Indeed, it is possible for a customer service ~~centre~~center to receive several tens of thousands of calls per day, and systematically, upon the arrival of each call, searching for the identifier in a database listing all the calls received during the day can consume a great deal of system resources.

~~The~~Our methods ~~proposed in the present invention~~make~~[[s]]~~ it possible to overcome this ~~disadvantage~~. Indeed, ~~[[it]]~~we provide~~[[s]]~~ a method of deducing statistics relating to call intents and recalls only according to statistics relating to calls received, disconnected and abandoned, which make up the default data supplied by the ACD (Automatic Call Dispatcher).

~~In order to do so, the present invention is of the type described above and is remarkable, in its broadest meaning, in that it relates to a~~We therefore provide methods of estimating call intents and recalls in a call ~~centre, characterised in that it comprises the following steps~~center comprising:

- (a) ~~[[to ]]~~assessing N corresponding to the number of periods during which the recall assessments are performed;

(b) [[to ]]assessing  $\alpha_i$  representing the proportion of disconnected calls that call back during the  $i^{\text{th}}$  period following disconnection;

(c) [[to ]]assessing  $\beta_i$  representing the proportion of abandoned calls that call back during the  $i^{\text{th}}$  period following abandonment;

(d) [[to ]]assessing the call status variables:

[[ - ]]  $Dec(p)$  representing the number of calls disconnected during a period p;

[[ - ]]  $Abd(p)$  representing the number of calls abandoned during a period p;

[[ - ]]  $Reçus(p)$  representing the number of calls received during a period p;

(e) ~~to estimate~~estimating the number of recalls,  $rappels(p)$ , during said period p, with

$$rappels(p) = \sum_{i=0}^N \alpha_i . dec(p-i) + \beta_i . abd(p-i), \text{ where } p-i \text{ represents the period}$$

that precedes p of i periods[[.]]; and

(f) [[to ]]assessing the number of call intents during a period p,  $intentions(p) = reçus(p) - rappels(p)$ .

***Kindly replace paragraphs [0015] through [0023] with the following:***

~~Said~~The estimation is advantageously performed without systematically recording the identifier of each call received.

The capacity of ~~said~~the call ~~center~~center is advantageously adapted according to ~~said~~the estimation.

~~The invention~~This disclosure also relates to a system for ~~the estimation of~~estimating call intents and recalls in a call ~~center~~center comprising calculation equipment connected to equipment associated with the call-answering stations, ~~characterised~~characterized in that the calculation

equipment comprises means for counting the number of disconnected calls *Dec*, the number of abandoned calls *Abd*, the number of received calls *Reçus* and calculation means for determining the coefficients  $\alpha_i$ ,  $\beta_i$  and  $N$ , as well as calculation means for determining the variables of the number of recalls and the number of call intents

$$rappels(p) = \sum_{i=0}^N \alpha_i \cdot dec(p-i) + \beta_i \cdot abd(p-i) \text{ and } intentions(p) = re\acute{c}us(p) - rappels(p),$$

[[W]]where  $N$  corresponds to the number of periods during which the assessment of recalls takes place;

$\alpha_i$  ~~representing the~~represents a proportion of disconnected calls that call back during the  $i^{\text{th}}$  period following disconnection;

$\beta_i$  ~~representing the~~represents a proportion of abandoned calls that call back during the  $i^{\text{th}}$  period following abandon; and

$p-i$  represents ~~the~~a period that precedes  $p$  of  $i$  periods.

~~The invention will be better understood from reading the following description, provided below by way of example, of an embodiment of the invention, made in reference to the appended figures, in which:~~

~~—— figure 1 shows the general principle of a call to the call centre;~~

~~—— figure 2 is a flowchart of the process of calling and of recalls for disconnections and abandons.~~

As shown in ~~figure~~Fig. 1, customer calls arrive first at a CTI (Computer Telephony Integration). According to information supplied by the ACD (Automatic Call Dispatcher) of each site, a routing mechanism makes it possible to decide to which site a call should be routed upon its arrival. Once the call is routed and if no customer service representative is able to answer it

immediately, it is placed on hold in a queue. The phenomena of abandonment and disconnection therefore complicate the management of such a call center.

Indeed, as shown in ~~figure~~Fig. 1, ~~let us consider~~there is a customer who decides to call the call center: this is a first call intent (1). This call can have several possible outcomes.

~~First of all~~, it can be placed in a queue (2) and then ~~[[be ]]~~answered by a customer service representative. This is ~~what we call~~ an answered call.

If it were possible in terms of available resources, all first call intents would be answered calls. However, a customer generally has to wait a short while before being answered by a customer service representative. It is possible, therefore, that such customer will prematurely end the call: this is an abandoned call (3).

***Kindly replace paragraph [0025] with the following:***

All the calls passed on to the customer centers, regardless of the nature of the call and its outcome, make up the received calls (8) (i.e. the total number of calls answered, abandoned or disconnected).

***Kindly replace paragraphs [0027] through [0029] with the following:***

Therefore, in a general fashion, it is possible by means of the ACD to assess the following parameters and variables for different periods:

$\alpha_i$  ~~representing the~~represents a proportion of disconnected calls that call back during the  $i^{\text{th}}$  period following disconnection,

$\beta_i$  ~~representing the~~represents a proportion of abandoned calls that call back during the  $i^{\text{th}}$  period following abandonment,

and N corresponds to the number of periods in which the recall assessments are conducted.



The different coefficients  $\alpha_i$  and  $\beta_i$  ~~characterise~~characterize the ~~behaviour~~behavior of the customer with regard to the call. These do not vary in real time and can be, for example, calculated using a linear regression method on a sample that is representative of the recall phenomenon during a “standard day” of the relevant call ~~cent~~center.

In addition, the call status statistics are assessed in real time over a period  $p$  using the ACDs. The following is then obtained for the period:

$Dec(p)$  representing the number of calls disconnected during a period  $p$ ;

$Abd(p)$  representing the number of calls abandoned during a period  $p$ ; and

$Reçus(p)$  representing the number of calls received during a period  $p$ [[;]].

***Kindly replace paragraphs [0032] through [0034] with the following:***

There are many foreseeable technical applications of this method of assessing the number of call intents. This ~~evidently~~ makes it possible, first of all, to size call ~~centres~~centers by adapting the number of sites or the number of customer service representatives. This sizing is then possible in overall terms as well as by periods.

Another application ~~would be~~is to reconstruct call intent histories according to the histories of calls received, abandoned and disconnected. Another usage is to allow an assessment of the quality of service with regard to call intents (rather than with regard to calls received). ~~The invention~~We make[[s]] it possible to perform this estimation in real time and to do so without ~~mobilising~~mobilizing considerable computing resources.

~~The invention~~This disclosure is described above by way of example. ~~It is obvious that these~~Those skilled in the ~~trade~~art will be able to implement various alternative ~~embodiments of the invention~~aspects without thereby departing from the ~~context of the patent~~scope of the appended claims.